TECHNICAL SPECIFICATION



QUARZ TIME SWITCH WITH POWER RESERVE

TM 181



The mechanic relay for time is supposed to be used for managing chains with maximum capacity of 3500W.After the setting, the timer executes the functions we required in 24 hours regime. The minimum period for setting is 30 minutes as it is executed within 48 pcs segments which the timing of the work and rest of the consummator is being set. The timer is accomplished with a battery which assures the work by 150 hours after power failure.

TECHNICAL SPECIFICATION




Technical data:

| Rated voltage: | 230-240V AC 50/60Hz | |
|-----------------------------|---|--|
| Time range: | 24 hours | |
| Min. programmable interval: | 30 minutes | |
| Time adjustment: | Manual | |
| Battery power reserve: | 150 hours | |
| Time deviation: | ± 1s (at 20°C) | |
| Consumption: | 2.5VA | |
| Contact: | 1NO | |
| Contact capacity: | 16A | |
| Electrical endurance: | 10 ⁵ times | |
| Mechanical endurance: | 10 ⁷ times | |
| Section of the conductor: | Rigid conductors up to 6mm ² | |

* **MOUNTING:** DIN-rail

Variants and dimensions:



| Туре | | Size | | Packing/box | Catalogue |
|--------|----|------|------|-------------|-----------|
| | | (mm) | | | number |
| | Н | L | D | (pcs) | |
| TM 181 | 90 | 54 | 60.5 | 1/ 100 | 50138 |

TECHNICAL SPECIFICATION



Standards:

EN 61812-1:2011

EN 60730-2-7:2010

