


LAMP PHOTOMETRIC REPORT

MODEL: 92EL62283030/WH		
POWER: 30W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 2761.9 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	1720	1715	1713	1715	1721	1726	1728	1725	0- 10	167.4	167.4	6.06
20	1536	1526	1524	1529	1538	1548	1550	1545	10- 20	461.0	628.4	22.8
30	1197	1181	1179	1191	1213	1229	1229	1218	20- 30	639.4	1268	45.9
40	737.5	719.3	721.2	736.2	754.1	772.8	771.3	757.4	30- 40	607.0	1875	67.9
50	369.2	362.6	360.6	368.0	382.8	390.1	392.3	385.3	40- 50	421.2	2296	83.1
60	178.1	174.4	171.8	176.0	180.8	184.0	183.5	183.2	50- 60	236.5	2533	91.7
70	106.4	102.1	98.57	103.5	107.7	106.6	104.0	107.1	60- 70	137.9	2670	96.7
80	43.00	37.91	33.78	38.84	41.76	41.00	38.06	41.75	70- 80	74.81	2745	99.4
90	0.7274	0.7115	0.6891	0.7232	0.6541	0.6367	0.6319	0.6361	80- 90	16.61	2762	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:06 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```