


LAMP PHOTOMETRIC REPORT

MODEL: 92EL62284240/WH		
POWER: 42W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 4199.8 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	2552	2546	2547	2552	2561	2563	2563	2557	0- 10	248.0	248.0	5.91
20	2309	2301	2301	2308	2322	2328	2329	2321	10- 20	689.4	937.4	22.3
30	1794	1774	1766	1768	1791	1812	1822	1815	20- 30	958.6	1896	45.1
40	1135	1119	1111	1115	1135	1152	1160	1155	30- 40	909.7	2806	66.8
50	596.5	583.3	577.2	579.9	592.9	606.5	613.8	610.4	40- 50	653.3	3459	82.4
60	287.6	280.4	276.4	278.2	284.8	290.6	292.9	293.7	50- 60	374.1	3833	91.3
70	166.7	162.1	157.2	162.4	167.6	168.1	165.1	167.9	60- 70	220.0	4053	96.5
80	67.28	63.13	58.85	63.97	67.26	64.50	63.01	63.82	70- 80	118.1	4171	99.3
90	1.172	1.159	1.128	1.169	1.044	1.043	1.016	1.032	80- 90	28.75	4200	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:06 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

