

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	3636.3 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	-2.5 degrees horizontal

Beam Spread	At 10% of Imax	50.2V x 50.0H
	At 50% of Imax	36.0V x 35.7H
	At 90% of Imax	19.4V x 19.2H

Beam Flux	Total	1218.1 lumens per klm.
	To 10% of Imax	1146.8 lumens per klm.
	To 50% of Imax	833.3 lumens per klm.
	To 90% of Imax	305.8 lumens per klm.

Upward LOR	0.0 %
Downward LOR	121.8 %


Luminaire Efficiency (Light Output Ratio)	121.5 %
---	---------

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 09 November 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: 93M20TL1230/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F42 x 165	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:



DATA OF LAMP		PHOTOMETRIC DATA	
MODEL	93M20TL1230/BL	Imax (cd)	3200
NOMINAL POWER (W)	12	AVAILABILITY (%)	114.6
RATED VOLTAGE (V)	48	Avai. FLUX (lm)	1009
NOMINAL FLUX (lm)	880	LOR (%)	121.5
LAMPS INSIDE	1	TOTAL FLUX (lm)	1069
TEST VOLTAGE (V)	48	θ @50% (H,V)	36,36DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.00
80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.21	0.00
70	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.03	0.03	0.03	0.03	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.58	0.00
60	0.00	0.00	0.00	0.01	0.02	0.04	0.06	0.08	0.09	0.09	0.08	0.06	0.04	0.02	0.01	0.00	0.00	0.00	1.20	0.00
50	0.00	0.00	0.00	0.02	0.04	0.07	0.12	0.16	0.18	0.19	0.16	0.12	0.08	0.04	0.02	0.00	0.00	0.00	2.70	0.00
40	0.00	0.00	0.01	0.03	0.06	0.12	0.21	0.35	0.54	0.55	0.37	0.23	0.13	0.07	0.03	0.01	0.00	0.00	35.1	23.1
30	0.00	0.00	0.01	0.04	0.09	0.19	0.55	4.47	12.8	12.0	4.07	0.58	0.20	0.09	0.04	0.01	0.00	0.00	188	181
20	0.00	0.00	0.01	0.04	0.11	0.29	4.19	31.2	60.5	58.7	28.5	3.93	0.31	0.12	0.05	0.01	0.00	0.00	317	311
10	0.00	0.00	0.01	0.05	0.12	0.44	11.3	58.7	91.1	88.7	55.0	10.6	0.46	0.14	0.05	0.02	0.00	0.00	313	307
0	0.00	0.00	0.01	0.05	0.13	0.46	10.6	57.8	90.5	88.0	54.6	10.0	0.48	0.15	0.06	0.02	0.00	0.00	176	169
-10	0.00	0.00	0.01	0.05	0.12	0.31	3.63	28.4	57.5	56.1	26.4	3.33	0.32	0.13	0.05	0.01	0.00	0.00	30.6	18.0
-20	0.00	0.00	0.01	0.04	0.09	0.20	0.61	3.89	11.1	10.2	3.48	0.60	0.21	0.10	0.04	0.01	0.00	0.00	2.69	0.00
-30	0.00	0.00	0.00	0.03	0.07	0.13	0.22	0.34	0.53	0.56	0.35	0.22	0.14	0.08	0.03	0.01	0.00	0.00	1.22	0.00
-40	0.00	0.00	0.00	0.02	0.04	0.07	0.12	0.16	0.18	0.18	0.16	0.13	0.09	0.05	0.02	0.00	0.00	0.00	0.59	0.00
-50	0.00	0.00	0.00	0.01	0.02	0.04	0.06	0.08	0.09	0.09	0.08	0.07	0.04	0.02	0.01	0.00	0.00	0.00	0.19	0.00
-60	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.03	0.03	0.03	0.03	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
HORIZONTAL (DEG)																				
Φ t	0.00	0.00	0.09	0.36	0.92	2.39	31.7	186	325	315	173	29.9	2.53	1.02	0.40	0.10	0.00	0.00	1069	---
Φ a	0.00	0.00	0.00	0.00	0.00	0.00	20.1	178	318	309	165	18.3	0.00	0.00	0.00	0.00	0.00	0.00	---	1009

one-half-peak spread: U:17.8,D:18.3 , L:15.7,R:20.2


NEMA Beam Type: Type 4

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:09 November 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME: 93M20TL1230/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F42 x 165	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 09 November 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME: 93M20TL1230/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F42 x 165	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 09 November 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 09 November 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

AAI Figure

NAME: 93M20TL1230/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F42 x 165	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:09 November 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 93M20TL1230/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F42 x 165	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-90	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-85	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-75	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.01	0.00	0.00
-70	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.05	0.09	0.15	0.20	0.26	0.31	0.32	0.32
-65	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.11	0.28	0.43	0.52	0.62	0.76	0.87	0.95	1.02	1.07
-60	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.07	0.27	0.47	0.60	0.86	1.08	1.24	1.41	1.59	1.71	1.77	1.78
-55	0.01	0.01	0.00	0.00	0.00	0.01	0.08	0.33	0.55	0.85	1.13	1.39	1.73	2.01	2.29	2.57	2.75	2.87	2.93
-50	0.01	0.01	0.00	0.00	0.00	0.05	0.26	0.56	0.94	1.25	1.67	2.09	2.58	3.01	3.36	3.75	4.03	4.21	4.29
-45	0.01	0.01	0.00	0.00	0.00	0.12	0.47	0.87	1.26	1.80	2.30	2.99	3.52	4.17	4.81	5.34	5.74	6.00	6.11
-40	0.01	0.01	0.00	0.00	0.01	0.27	0.65	1.18	1.73	2.33	3.13	3.88	4.81	5.70	6.59	7.38	7.97	8.31	8.43
-35	0.01	0.01	0.01	0.00	0.06	0.41	0.93	1.46	2.15	3.04	3.91	5.07	6.23	7.69	8.98	10.3	12.2	13.2	13.5
-30	0.01	0.01	0.01	0.00	0.10	0.53	1.14	1.84	2.66	3.63	4.89	6.29	8.18	10.3	14.0	21.3	35.1	48.5	56.0
-25	0.01	0.01	0.01	0.00	0.17	0.64	1.29	2.11	3.16	4.21	5.85	7.88	10.5	16.4	38.2	91.1	211	279	299
-20	0.01	0.01	0.01	0.01	0.25	0.79	1.47	2.34	3.52	4.94	6.82	9.45	14.6	37.3	122	337	741	1020	1117
-15	0.01	0.01	0.01	0.01	0.31	0.90	1.64	2.62	3.84	5.52	7.73	11.0	22.4	92.0	338	958	1580	1980	2100
-10	0.01	0.01	0.01	0.01	0.36	0.97	1.74	2.73	3.98	5.91	8.46	13.2	36.4	184	741	1609	2316	2723	2820
-5	0.01	0.01	0.01	0.01	0.39	1.01	1.78	2.73	3.92	5.84	8.64	14.4	49.2	285	1076	2032	2773	3071	3090
0	0.01	0.01	0.01	0.01	0.40	1.01	1.76	2.66	3.76	5.60	8.38	14.2	52.2	332	1220	2210	2931	3188	3182
5	0.01	0.01	0.01	0.02	0.39	0.99	1.74	2.63	3.74	5.54	8.23	13.7	46.1	303	1127	2073	2781	3084	3123
10	0.01	0.01	0.01	0.02	0.37	0.95	1.67	2.55	3.65	5.32	7.79	12.4	32.9	246	830	1666	2382	2768	2864
15	0.01	0.01	0.01	0.02	0.33	0.88	1.57	2.40	3.49	5.01	7.10	10.4	19.5	91.3	407	1068	1676	2074	2192
20	0.01	0.01	0.02	0.02	0.28	0.79	1.44	2.21	3.26	4.54	6.31	8.83	13.6	29.5	163	410	847	1156	1237
25	0.01	0.01	0.02	0.02	0.21	0.68	1.29	2.00	2.91	3.96	5.46	7.41	10.2	15.2	29.1	111	220	337	351
30	0.01	0.01	0.02	0.02	0.14	0.57	1.09	1.75	2.54	3.50	4.62	5.99	7.92	10.3	14.0	19.9	31.2	42.6	45.8
35	0.01	0.01	0.02	0.02	0.09	0.43	0.89	1.52	2.16	2.97	3.82	4.85	6.02	7.58	9.13	11.1	13.4	15.0	15.4
40	0.01	0.01	0.02	0.02	0.03	0.29	0.70	1.19	1.78	2.41	3.11	3.84	4.63	5.53	6.56	7.45	8.27	8.82	8.99
45	0.01	0.01	0.02	0.02	0.02	0.14	0.48	0.88	1.41	1.86	2.40	2.98	3.53	4.10	4.69	5.19	5.65	5.95	6.05
50	0.01	0.01	0.02	0.02	0.02	0.05	0.27	0.62	0.94	1.42	1.78	2.21	2.64	3.04	3.40	3.70	3.91	4.03	4.07
55	0.01	0.01	0.02	0.02	0.02	0.01	0.11	0.33	0.62	0.88	1.23	1.61	1.82	2.14	2.40	2.59	2.74	2.83	2.85
60	0.01	0.01	0.02	0.02	0.01	0.02	0.02	0.12	0.28	0.49	0.75	0.94	1.16	1.43	1.60	1.70	1.77	1.81	1.83
65	0.01	0.01	0.02	0.02	0.01	0.01	0.02	0.02	0.06	0.16	0.31	0.45	0.61	0.78	0.89	0.96	0.99	1.04	1.07
70	0.01	0.01	0.02	0.02	0.01	0.01	0.02	0.02	0.02	0.02	0.04	0.10	0.16	0.23	0.31	0.36	0.39	0.42	0.44
75	0.01	0.01	0.02	0.02	0.02	0.02	0.02	0.02	0.01	0.01	0.02	0.02	0.01	0.02	0.03	0.02	0.01	0.02	0.03
80	0.01	0.01	0.02	0.02	0.02	0.02	0.02	0.02	0.01	0.02	0.02	0.02	0.01	0.02	0.02	0.02	0.01	0.01	0.02
85	0.01	0.01	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.01	0.01	0.01	0.02	0.02	0.02	0.01
90	0.01	0.01	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.01	0.01	0.02	0.02	0.02	0.01

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:09 November 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 93M20TL1230/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F42 x 165	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-75	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-70	0.34	0.33	0.27	0.20	0.13	0.06	0.04	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-65	1.09	1.06	1.00	0.89	0.74	0.57	0.37	0.22	0.07	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-60	1.83	1.82	1.75	1.62	1.47	1.30	1.07	0.75	0.47	0.22	0.06	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-55	2.93	2.86	2.72	2.47	2.31	2.14	1.73	1.40	1.03	0.62	0.27	0.06	0.01	0.00	0.00	0.00	0.00	0.00	
-50	4.29	4.17	3.95	3.64	3.43	3.04	2.58	2.17	1.55	1.14	0.63	0.23	0.04	0.00	0.00	0.00	0.00	0.00	
-45	6.04	5.85	5.54	5.10	4.58	3.99	3.56	2.88	2.35	1.56	1.05	0.49	0.09	0.00	0.00	0.00	0.00	0.00	
-40	8.29	8.00	7.45	6.75	6.03	5.27	4.42	3.70	2.90	2.22	1.43	0.80	0.25	0.01	0.00	0.00	0.00	0.00	
-35	13.1	12.0	10.3	9.01	7.84	6.64	5.55	4.45	3.59	2.65	1.80	1.10	0.42	0.05	0.00	0.00	0.00	0.00	
-30	53.8	40.1	22.7	13.5	10.3	8.40	6.78	5.38	4.08	3.10	2.23	1.34	0.64	0.09	0.00	0.00	0.00	0.00	
-25	256	168	85.1	38.1	15.7	10.5	8.14	6.34	4.74	3.53	2.45	1.52	0.83	0.16	0.00	0.00	0.00	0.00	
-20	979	638	302	105	37.5	14.3	9.70	7.24	5.41	3.88	2.63	1.69	0.97	0.24	0.00	0.00	0.00	0.00	
-15	1932	1508	879	304	84.1	22.9	11.4	8.09	5.98	4.23	2.87	1.85	1.07	0.30	0.00	0.00	0.00	0.00	
-10	2643	2205	1517	695	167	36.5	13.7	8.94	6.41	4.49	3.05	1.96	1.13	0.35	0.01	0.00	0.00	0.00	
-5	2971	2647	1915	1011	270	47.6	15.4	9.48	6.67	4.63	3.15	2.01	1.15	0.38	0.01	0.00	0.00	0.00	
0	3072	2792	2073	1120	311	49.7	16.0	9.70	6.75	4.65	3.16	2.01	1.15	0.39	0.01	0.00	0.00	0.00	
5	3008	2650	1945	1030	292	44.5	15.2	9.15	6.35	4.39	3.03	1.95	1.13	0.39	0.01	0.00	0.00	0.00	
10	2698	2247	1550	746	232	33.4	13.6	8.42	5.76	4.03	2.83	1.85	1.08	0.36	0.01	0.00	0.00	0.00	
15	2010	1587	956	361	92.6	21.0	11.4	7.70	5.34	3.71	2.57	1.73	1.01	0.33	0.01	0.00	0.00	0.00	
20	1105	762	357	149	31.7	14.9	9.58	6.81	4.82	3.41	2.34	1.61	0.92	0.27	0.01	0.00	0.00	0.00	
25	306	199	105	31.5	16.6	10.9	8.00	5.82	4.19	3.13	2.12	1.45	0.82	0.20	0.01	0.01	0.00	0.00	
30	43.6	33.1	21.5	15.1	11.0	8.47	6.42	4.84	3.61	2.71	1.88	1.23	0.65	0.13	0.01	0.01	0.00	0.00	
35	15.2	13.8	11.5	9.71	7.99	6.44	5.06	3.94	3.10	2.24	1.65	1.02	0.45	0.08	0.01	0.01	0.00	0.00	
40	8.95	8.51	7.73	6.90	5.86	4.81	3.93	3.22	2.46	1.81	1.31	0.84	0.29	0.03	0.01	0.01	0.00	0.00	
45	6.09	5.88	5.45	4.86	4.17	3.62	3.10	2.42	1.86	1.46	1.00	0.54	0.13	0.02	0.01	0.01	0.00	0.00	
50	4.06	3.96	3.77	3.49	3.14	2.68	2.18	1.78	1.45	1.05	0.70	0.28	0.05	0.02	0.01	0.01	0.01	0.00	
55	2.84	2.76	2.58	2.34	2.12	1.82	1.58	1.29	0.98	0.69	0.35	0.10	0.01	0.01	0.01	0.01	0.01	0.00	
60	1.82	1.78	1.70	1.60	1.45	1.22	1.02	0.82	0.54	0.29	0.11	0.02	0.01	0.01	0.01	0.01	0.01	0.00	
65	1.07	1.04	1.01	0.94	0.83	0.67	0.49	0.32	0.14	0.06	0.02	0.02	0.01	0.01	0.01	0.01	0.01	0.00	
70	0.43	0.41	0.38	0.32	0.23	0.15	0.10	0.03	0.02	0.01	0.02	0.02	0.01	0.01	0.01	0.01	0.01	0.00	
75	0.02	0.01	0.02	0.03	0.02	0.01	0.02	0.02	0.02	0.01	0.02	0.02	0.01	0.01	0.01	0.01	0.01	0.00	
80	0.01	0.01	0.01	0.02	0.01	0.01	0.01	0.01	0.01	0.01	0.02	0.02	0.01	0.01	0.01	0.01	0.01	0.00	
85	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.02	0.02	0.01	0.01	0.01	0.01	0.00	
90	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.02	0.02	0.02	0.01	0.01	0.01	0.00	

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:09 November 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks: