


LAMP PHOTOMETRIC REPORT

MODEL: 996GRFLED070/T3		
POWER: 7W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 55.656 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	32.92	36.57	35.64	24.08	27.28	19.20	22.57	36.91	0- 10	1.373	1.373	2.47
20	31.62	35.35	39.00	22.60	41.14	38.84	30.08	49.30	10- 20	10.06	11.44	20.6
30	16.78	17.60	15.00	14.49	18.62	25.06	17.59	18.42	20- 30	12.05	23.49	42.2
40	15.08	12.17	12.66	14.54	15.85	12.96	12.49	15.51	30- 40	10.89	34.38	61.8
50	9.775	6.177	5.692	9.452	9.602	7.058	8.446	9.833	40- 50	8.334	42.71	76.7
60	5.478	4.298	4.187	5.191	6.999	4.622	5.069	6.922	50- 60	6.288	49.00	88
70	2.668	3.579	2.601	2.318	4.411	2.568	4.102	3.852	60- 70	4.325	53.33	95.8
80	0.5253	0.7746	0.6020	0.5314	0.9347	0.5592	0.7180	0.9998	70- 80	1.968	55.29	99.3
90	0.1461	0.1507	0.0327	0.1091	0.2436	0.0923	0.0682	0.1746	80- 90	0.3624	55.66	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 06 October 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```